

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: KEYSTONE LIQUID OIL ORANGE HF LB514

Product code: 506 702 50

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Keystone Europe Ltd©
Units 1-2 Beckview Business Parks
Leeds Road
Huddersfield
HD2 1UR
United Kingdom

Tel: 01484 341 466

Fax: 01484 341 544

Email: reach@keystone-europe.co.uk

1.4. Emergency telephone number

Emergency tel: +1 813 248 0585

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT RE 2: H373; Aquatic Chronic 2: H411; Repr. 2: H361f; STOT SE 2: H371

Most important adverse effects: Suspected of damaging fertility. May cause damage to organs . May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H361f: Suspected of damaging fertility.

H371: May cause damage to organs .

H373: May cause damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS08: Health hazard

GHS09: Environmental



SAFETY DATA SHEET
KEYSTONE LIQUID OIL ORANGE HF LB514

Page: 2

Precautionary statements: P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P308+313: IF exposed or concerned: Get medical attention.
P309+311: IF exposed or if you feel unwell: Call a POISON CENTRE or doctor.
P314: Get medical attention if you feel unwell.

2.3. Other hazards

Other hazards: Danger of serious damage to health by prolonged exposure.
PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

KEROSINE - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), HEAVY AROM.

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-198-5	64742-94-5	-	Asp. Tox. 1: H304; Aquatic Chronic 2: H411	50-70%

SOLVENT RED 164.

296-120-8	92257-31-3	-	Repr. 2: H361f; STOT SE 2: H371; STOT RE 2: H373	10-30%
-----------	------------	---	--	--------

NAPHTHALENE

202-049-5	91-20-3	-	Carc. 2: H351; Acute Tox. 4: H302; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%
-----------	---------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK,

[cont...]